



**Hole Digging Equipment**  
**HAND HELD**

**Blanchard Machinery Inc.**  
1890 N.E. 150 Street  
North Miami Fla.33181  
bmisalz@aol.com  
www.blanchardmachinery.net



## 357H TWO MAN HOLE DIGGER

The time proven 300 Series Hole Diggers are designed to tackle a wide range of construction related hole digging projects...from simple backyard fencing to complex landscaping and soil sampling. Each built with oversized bearings, heat treated shafts and precision, machine cut gears that has created an industry wide reputation for delivering long service life and exceptional ROI. Each with the power and performance to dig up to 18 inch diameter (457 mm) diameter holes in a wide variety of soil classifications. The unique Comfort-Flex™ operator handles actually flex under load to help absorb vibration and kickback forces encountered. This feature dramatically reduces operator fatigue, increases productivity rates and enhances jobsite safety. For use with the BT360 Series earth augers and auger extension.

### FEATURES

- All metal centrifugal clutch
- Precision, spur gear transmission
- Comfort-Flex™ operator handles
- Magura® twist grip throttle control

### SPECIFICATIONS

<b>Engine</b>	5.5 HP (4.1 kw) Honda GXV160, 4-stroke
<b>Starter</b>	Hand rewind
<b>Fuel</b>	Gasoline, unleaded, automotive grade
<b>Transmission</b>	Totally enclosed, spur gear, oil lubricated
<b>Maximum Digging Torque</b>	190 ft lbs (225 N.m)
<b>Nominal Auger Rotation Speed</b>	144 RPM, no load
<b>Auger Drive Connection</b>	STIHL® type configuration
<b>Available Auger Diameter Range</b>	4 inch (102 mm) to 18 inch (457 mm)
<b>Standard Auger Digging Length</b>	30 inch (762 mm)
<b>Available Auger Extension</b>	15 inch (381 mm), plain-tube type
<b>Weight (less auger)</b>	71 lbs (32 kg)



All specifications are general in nature and are not intended for specific application purposes. General Equipment Company reserves the right to make changes in design, engineering, or specifications and to add improvements or discontinue manufacture at any time without notice or obligation. Consult applicable Operator Manual before utilizing. Refer to OSHA 2207 and/or current revisions for specific safety information. Names depicted are the registered trademarks of their respective owners.