



**SURFACE PREPARATION**  
**ROTARY ASPHALT CUTTERS**  
 C Series



**130C CUT-R-TACH® CLAMP MOUNT ATTACHMENT**

The C Series CUT-R-TACH Rotary Asphalt Cutting Attachments quickly attach to a wide variety of backhoes, tractor/wheel loaders and similar prime mover vehicles for cutting throughout high density asphaltic materials. Designed to accommodate a wide range of bucket and tooth configurations up to 2-1/2 inches (63 mm) maximum height and 6 inches (153 mm) width. Produces smooth-sided cuts up to 5 inches (127 mm) deep at rates approaching 6000 lineal feet (1.8 km) per hour. The C Series models each feature a counter-rotating, twin-screw, clamping system that retains the unit tight in both forward and reverse cutting directions. Special, heat-treated, alloy-steel cutting blade is self-sharpening. Quickly field replaced without disturbing bearings or seals. No special installation tools are required for mounting.

**FEATURES**

- Unitized, welded steel frame
- Patented clamp system
- High capacity, maintenance-free, sleeve-type bearings
- Self-sharpening blade

**SPECIFICATIONS**

<b>Frame</b>	Utilized, welded steel plate
<b>Cutting Blade Diameter</b>	13-1/2 inches (343 mm)
<b>Hub Assembly</b>	Alloy steel axle with machined hub
<b>Bearings</b>	Sleeve type
<b>Mounting</b>	Twin pivoting clamping screws
<b>Maximum Downforce</b>	25,000 lbs (11,000 kg)
<b>Cutting Depth</b>	5 inches (127 mm)
<b>Weight</b>	145 lbs (64 kg)



RENTAL / SALES / SERVICE

**Blanchard Machinery Inc.**  
 1890 N.E. 150 Street  
 North Miami Fla. 33181  
 bmisalz@aol.com  
 www.blanchardmachinery.net

All specifications are general in nature and are not intended for specific application purposes. General Equipment Company reserves the right to make changes in design, engineering, or specifications and to add improvements or discontinue manufacture at any time without notice or obligation. Consult applicable Operator Manual before utilizing. Refer to OSHA 2207 and/or current revisions for specific safety information. Names depicted are the registered trademarks of their respective owners.