

SG24/E3HP60 DUAL HEAD SURFACE GRINDER

The SG24 Series Surface Grinders were designed for targeted usage by contractors and homeowners alike for those job applications where additional capacity and productivity are required. Available with electric, gasoline and propane power source options. Designed for breaking up deposits of grease, dirt, rubber carpet backing and industrial residues from floors; cleaning concrete, asphalt and tiles; producting exposed, decorative slabs along with a wide range of general concrete grinding job applications. The dual, counter-rotating, multi-accessory discs balance forces to help reduce operator fatigue and enhance machine control. The SG24 Series accommodate a wide range of industry-standard, interchangeable attachments including grinding stones, scarifiers, wire brushes, the SCRAPE-R-TACH[®] Coatings Removal System, the DIAM-A-TACH[®] Diamond Grinding System and Pro Polish[™] Concrete Floor Polishing System for unmatched versatility and productivity.

FEATURES

- 230 VAC, single phase operation
- Central lubrication system
- Adjustable operator handle
- Integral V-belt tension system
- Accepts industry-type attachments

SPECIFICATIONS

| Power Source | 3 HP (2.3 kw), 115 VAC, 60 HZ, 1 phase. Can be field wired for 230 VAC operation. |
|---------------------------------------|--|
| Frame | Unitized, welded steel plate |
| Drive System | V-belt/spur gear-type reduction |
| Multi-Accessory Disc Configuration | Two each, aluminum, 12 inch (305 mm) diameter, direct attachment mount with plastic wedges |
| Nominal Disc Rotation Speed | 250 RPM |
| Dust Port Connection | 3 inch (76 mm) diameter |
| Dimensions | Width: 37-1/2 inches (699 mm) Height: 38 inches (965 mm) Length: 55-1/4 inches (1403 mm) |
| Weight | 295 lbs (134 kg) |

All specifications are general in nature and are not intended for specific application purposes. General Equipment Company reserves the right to make changes in design, engineering, or specifications and to add improvements or discontinue manufacture at any time without notice or obligation. Consult applicable Operator Manual before utilizing. Refer to OSHA 2207 and/or current revisions for specific safety information. Names depicted are the registered trademarks of their respective owners.