







## SP8/E5HP60 SURFACE PLANER

Designed for a wide range of concrete removal, repair or restoration job applications. The exclusive drum forward configuration was specifically designed for sidewalk trip and fall type removal projects. Welded, unitized frame construction with full length, hexagon driveshaft for maximum power transmission to the flail drum. Extra capacity, ball bearings are externally greased to extend their service life. The Quik-Pitch® lever/drum engagement system features a separate, fine adjustment for precise control. Standard 8 inch (203 mm) drum width and 5/8 inch (16 mm) maximum cutting depth. An industry standard 3 inch (76 mm) diameter vacuum system port is provided for use with appropriate industrial type, dust control systems. Includes one drum, less flail kit.

## **FEATURES**

- External bearing lubrication system
- Quik-Pitch™ engagement system
- Fine pitch drum control system
- Full length hexagon driveshaft

Blanchard Machinery Inc. 1890 N.E. 150 Street North Miami Fla.33181 bmisalz@aol.com www.blanchardmachinery.net 1-800-330-4242

## **SPECIFICATIONS**

Power Source	5 HP (3.7 kw), 3450 RPM, 230 VAC 60 HZ, 1 phase
Frame	Unitized, welded steel plate
Bearings	High-capacity, double-row, ball type
Driveshaft Configuration	13/16 inch (21 mm) full length hexagon
<b>Cutting Depth Adjustment</b>	Screw type with Quik-Pitch® system
Maximum Cutting Depth	5/8 inch (16 mm)
Maximum Cutting Width	8 inch (203 mm)
<b>Dust Port Connection</b>	3 inch (76 mm) diameter
Dimensions	Width: 17-1/2" (419 mm) Height: 39-1/2" (1003 mm) Length: 39-1/4" (997 mm)
Weight	195 lbs (88 kg), less drum/flail kit

All specifications are general in nature and are not intended for specific application purposes. General Equipment Company reserves the right to make changes in design, engineering, or specifications and to add improvements or discontinue manufacture at any time without notice or obligation. Consult applicable Operator Manual before utilizing. Refer to OSHA 2207 and/or current revisions for specific safety information. Names depicted are the registered trademarks of their respective owners.

Form: GEF01111029